Excel in Your Field

Specifications

CATEGORY	XP8084	XP8084CPS	XP8101CPS
ENGINE			
Туре	4Cylinder, CRDI, Water-cooled		
Model	F5G		
Emission		Tier4 Final	
Engine HP, kW	84.5 (63)	84.5 (63)	100.6 (75)
PTO, HP	71.8	71.8	85.5
Rated speed, rpm		2,200	
Displacement, in ³		206.7	
Fuel tank capacity, gal		30.4	
DRIVE TRAIN			
Transmission type (option)	Synchro Shuttle	Power Shuttle	Power Shuttle
No. of speed	20 x 20	40 x 40	40 x 40
Forward speed, mph	0.1 ~ 20.8	0.09 ~21.1	0.1 ~ 22.6
PTO			
Туре	Independent / Ground Speed PTO		
Rear, rpm	540 / 750 / 1,000		
HYDRAULIC SYSTEM			
Control system	Position / Draft		
Implement pump, gpm	15.7		
Steering pump, gpm	6.5		
Total flow, gpm	22.2		
Category, 3pt hitch		CAT II	
Hitch lift capacity, lbs	7,275	7,275	8,378
Remote ports	2 pairs (Front), 3 pairs (Rear)	3 pairs (Front), 3 pairs (Rear)	3 pairs (Front), 3 pairs (Rear)
DIMENSION			
Overall length, Frame to link, in		152.2	
Overall width with tires, in	78.8	78.8	78.7
Wheelbase, in		90	
Height to top, in	106.3	103.4	105.4
Total weight without ballast, lbs	6,771	7,525	7,714
TIRE SIZE			
Front	12.4 - 24	12.4 - 24	13.6 - 24
Rear	18.4 - 30	18.4 - 30	18.4 - 34

Front end Loader	LL8100
Tractor Application	XP Series
Bucket Size, in.	83
Maximum Lift Heigh, in.	139.9
Clearance with Attachment Dump, in.	103.3
Reach at Maximum Height, in.	23.4
Maximum Dump Angle, deg.	57
Maximum Rollback Angle, deg.	46
Digging Depth, in.	4.6
Overall Height in Carry Position, in.	68.8
Lift Capacity (@ Pivot pin), lbs.	5,139
Breakout Force (@ Pivot pin), lbs.	5,313
Approx. Weight (Loader w/o Bucket), lbs.	1,660

Additional Equipment on Cab Models

- · Deluxe cab with AC and heat
- Cabin air recirculation
- Front & rear windshield washer/wipers
- · Deluxe stereo system with CD Player

Note Specifications and design are subject to change without prior notice.

Power & tilt steering

Get More Standard Features

- Switch operated Independent PTO with 540, 750 & 1000

 RPM
- Front loader valve and fender mounted joystick
- Clock
- Deluxe adjustable seat
- Remote control valves (3 pair)
- Rear work light
- Horn
- 7 pin electrical connector
- Extendable lower links and telescopic stabilizers
- Draw bar

- Hydraulic draft & position control with auto lift
- Pre-heat starting aid
- Hand & foot accelerator control
- Safety flashers & turn signals
- Fuel, coolant temperature, tachometer & hour meter gauges
- Differential lock, parking brake, battery charging, engine oil pressure, fuel filter, hydraulic oil filter pressure, 4WD, PTO operation, high beam operation /warning lights





P: 252.984.0700 | F: 252.984.0701 | www.lstractorusa.com

Dealer Imprint Zone

39000953 - 1612



XP8000 Series

XP8084 / XP8084CPS / XP8101CPS
Heavy Duty Utility Tractors



- Eco-Friendly Tier4 Engine
- 5 year warranty*
- 20x20 fully synchronized shuttle shift (Open station) or 40x40 power shuttle (Cab models)
- Creeper gear
- Front wheel mechanical assist 4WD
- 3 Pair of remote valves with float & detent functions
- Selectable 540, 750 & 1000 RPM rear Independent PTO
- Available with quick attach, self-leveling front end loader with skid steer compatible bucket & grill guard

* 6-year limited See dealer for details