

MT2S SERIES

# LS Tractor



MT225s  
PREMIUM COMPACT TRACTORS

6-YEAR LIMITED WARRANTY. SEE DEALER FOR DETAILS

# MT2S SERIES

PREMIUM COMPACT TRACTORS

## RECOMMENDED IMPLEMENTS/ ATTACHMENTS



**LOADER:**  
High Capacity With  
An Abundance Of  
Standard Features



**BACKHOE:**  
Excellent Capacity,  
Smooth And  
Consistent Operation  
For Added Control



**ROTARY CUTTER:**  
Durable Heavy Steel  
Design Providing  
Quality And Strength



**BOX BLADE:**  
Features A Heavy  
Welded Steel  
Design For Use In  
Demanding Applications

## FEATURES

- **6 Year Warranty\***
- **24.7 HP Yanmar Diesel Engine**
- **3 Range Hydrostatic Transmission (2 Pedal)**
- **Electric Engagement Independent PTO**
- **New Heavy-Duty Platform/Frame**



**Premium Reversible Seat**  
Adjustable Foldable  
Armrest, Tilt High Back Seat.  
\*Reversible Seat Only On  
Backhoe Models



**3 Range Hydrostatic  
Transmission**  
(2 Pedal) Comfortable And  
Efficient Operator Control



**Bolted Edge Bucket**  
Built For The  
Harshest Conditions



**Standard Factory Grille  
Guard W/ Loader**  
Full Length Grille Guard  
Protect Body Panels  
And Radiator



**Optional Thumb  
Configuration Backhoe**  
Provides Added Functionality  
To The Heavy-Duty Backhoe



**Optional Drive-Over  
Mid-Mount Mower Deck**  
Providing Convenience And  
Ease Of Adapting To Any  
Application



**Standard Tilt Steering**  
Provides Enhanced  
Operator Comfort



**Standard Foldable ROPS**  
Enables Easy Adjustment  
For Clearance



**Mid-Mount Mower  
Height Adjustment Dial**  
Enables Precise Height  
Control Of The Mid-Mount  
Mower, By A Simple Turn

# MT225s



## SPECIFICATIONS

CATEGORY	
ENGINE	MT225s
Type	3 Cylinder-IDI
Model (Tier 4)	3TNV80F-ZXKLST (Yanmar)
Engine HP (gross)	24.7
PTO (HP)	19.3
Rated Speed (rpm)	2,800
Displacement-cu (in <sup>3</sup> .)	77.3
Fuel Tank Capacity (gal.)	6.79
Alternator (V-A)	12 - 40
DRIVE TRAIN	
Transmission	HST
No. Of Speed	3 Ranges
Brakes	Wet, Multi-disc
PTO	
Type	Independent
Rear (rpm)	540
Mid PTO (Option)	2,500
HYDRAULIC SYSTEM	
Lift Control System	Position
Implement Pump (gpm)	5.6
Steering Pump (gpm)	3.7
Steering	Hydrostatic Power Steering
Total Flow (gpm)	9.3
Category (3pt Hitch)	CAT I
Hitch Lift Capacity (lbs.) (Hitch End)	1,896
Remote Valves	1 Pair (Option)
DIMENSION (with R1 tires)	
Overall Length (Frame To Link in.)	111.9
Overall Width With Tires (in.)	48.7
Wheelbase (in.)	63.4
Height To Top Of ROPS (in.)	86.4
TIRE SIZE	
Front / Rear Ag (R1)	7 - 12 / 11.2 - 16
Front / Rear Industrial (R4)	23 x 8.5 - 12 / 12 - 16.5
Front / Rear Turf (R3)	22 x 8.5 - 12 / 31 x 15.5 - 15
WEIGHT	
Total Weight w/o Ballast (lbs.)	1,764

*\*All Specs and features are subject to change, and pictures could include optional equipment etc.*

FRONT END LOADER		LL2300
TRACTOR APPLICATION		MT225s
Bucket Size (in.)		54.3
Maximum Lift Height (in.)		84.4
Clearance With Attachment Dump (in.)		59.1
Reach At Maximum Height (in.)		17.9
Maximum Dump Angle (deg.)		55
Maximum Rollback Angle (deg.)		40
Digging Depth (in.)		4.5
Overall Heights In Carry Position (in.)		46
Lift Capacity (At Pivot Pin) (lbs.)		1,067
Breakout Force (At Pivot Pin) (lbs.)		2,290
Approx. Weight (Loader w/o Bucket) (lbs.)		708

BACKHOE		LB1300
TRACTOR APPLICATION		MT225s
Digging Depth (in.)		84.9
Reach From Centerline Of Swing Pivot (in.)		113.7
Loading Height (in.)		64.7
Swing Arc (deg.)		180
Transport Height (in.)		73.4
Bucket Rotating (deg.)		177
Stabilizer Spread (Down Position) (in.)		82.2
Stabilizer Spread (Up Position) (in.)		65.4
Bucket Digging Force (lbs.)		3,013

MID MOWER		LM2360
TRACTOR APPLICATION		MT225s
Cutting Width (in.)		60
Cutting Height Range (in.)		1 - 4
Transport Height (in.)		6
Gear Type		Spiral Bevel
Number Of Blades		3
Adjustment Of Cutting Height		Dial
Deck Thickness (in.)		0.15
Total Width (in.)		75.7
Total Length (w/o Linkage)		44.1
Total Height (w/o Linkage)		11.9
Lifting Type		3-Point Upper Link
Total Weight (lbs.)		368

### Additional Equipment

- Standard Factory Toolbox
- Standard 12 Volt Power Outlet
- Flat Operator With Rubber Mat
- Standard Factory Platform Step



# LS Tractor

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | [LSTractorUSA.com](http://LSTractorUSA.com)  
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

