

RECOMMENDED IMPLEMENTS/ **ATTACHMENTS**



LOADER: **High Capacity With** An Abundance Of **Standard Features**



LAND GRADER: **Heavy Steel** Construction, High Strength, Designed For Use In Demanding **Applications**



ROTARY CUTTER: Durable Heavy Steel Design Providing Quality And Strength



BOX BLADE: Features A Heavy Welded Steel Design For Use In Demanding Applications

FEATURES

- 6 Year Warranty*
- → 16F x 16R Fully Synchronized Shuttle Shift or 16F x 16R Power Shuttle Shift (CPS Models) Transmission
- **Backhoe Compatible**
- Premium Ergonomically Designed Cab
- Standard High Capacity Three-Point And Loader Lift Capacity



Available With Three Rear Remotes (Cab Only) Provides Added Flexibility For Attachments And **Implements**



Standard Ground Control Three-Point Adjustment Provides Ground Controllability Of Three-Point Position To **Enable Easier Connectively** With Implements



Standard Right-Side Cab **Door With Steps Provides Additional Access** To The Operators Platform



Standard Telescopic Link Arms **Enables Connecting Three-Point Implements** Easier



Standard Drawbar Added Value Of Providing **Essential Heavy-Duty** Features



Standard Grille Guard With **Loader And Position ROD** Protects Grille And Radiator In Loader Applications



Standard Large Adjustable Mirrors Provide Visibility In A Variety Of Applications



Ground Level Fuel Tank Provides Easier Fueling Access



Variety Of Tires To Choose, **Including Titan Tires** Provides A Variety Of Tread Patterns And Sizes To Accommodate Customer Applications



SPECIFICATIONS

CATEGORY					
ENGINE	MT458	MT458CPS	MT468	MT468C	MT468CPS
Туре	4Cylinde	er In-line Vertical, \		d 4cycle Turb	o Diesel, CRDI
Model (Tier 4)			L4C25-T		
Engine HP (gross)		58		68	
PTO (HP)		51.2		60	
Rated Speed (rpm)			2,500		
Displacement (in ³ .)	152.8				
Fuel Tank Capacity (gal.)	21.1				
Alternator (V-A)	12-70				
DRIVE TRAIN					
Transmission	Synchro Shuttle / Power Shuttle (CPS Models)				
No. Of Speed	F16 x R16				
Brakes	Wet, Multi-disc				
PTO					
Туре	Independent				
Rear (rpm)	540				
HYDRAULIC SYSTEM					
Control System	Position / Draft				
Implement Pump (gpm)	9.9				
Steering Pump (gpm)	4.6				
Steering	Hydrostatic Power Steering				
Total Flow (gpm)	14.5				
Category (3pt Hitch)	CAT II				
Hitch Lift Capacity (Hitch End) (Ibs.)	4,079				
Remote Valves	2 Pairs Standard				
DIMENSION					
Overall Length (Bumper To Link in.)			138.6		
Overall Width With Tires (in.)	70				
Wheelbase (in.)	80.3				
Height To Top Of ROPS (in.)	103	100.6	103		100.6
TIRE SIZE					
Front / Rear Ag	9.5 - 20 / 16.9 - 24				
Front / Rear Industrial	10.5 / 80 - 18, 19.5L - 24				
Front / Rear Turf	36 x 13.5 - 15, 16.9 - 24				
WEIGHT		30 X		2-	
Total Weight w/o Ballast (lbs.)	4,674	5,121	4,674		5,121
Total Proight W/O Dallast (IDS.)	4,074	5,121	4,074		U, 12 1

^{*}All Specs and features are subject to change, and pictures could include optional equipment etc.

FRONT END LOADER	LL5106
TRACTOR APPLICATION	MT4 SERIES
Bucket Size (in.)	72
Maximum Lift Height (in.)	116.3
Clearance With Attachment Dump (in.)	82.8
Reach At Maximum Height (in.)	6.6
Maximum Dump Angle (deg.)	72
Maximum Rollback Angle (deg.)	46
Digging Depth (in.)	4.2
Overall Height In Carry Position (in.)	68.9
Lift Capacity (At Pivot Pin) (Ibs.)	2,981
Breakout Force (At Pivot Pin) (lbs.)	4,767

BACKHOE	LB3102
TRACTOR APPLICATION	MT4 SERIES
Digging Depth (in.)	94.5
Reach From Centerline Of Swing Pivot (in.)	136.2
Loading Height (in.)	80.3
Swing Arc (deg.)	180
Transport Height (in.)	92.9
Bucket Rotating (deg.)	180
Stabilizer Spread (Down Position) (in.)	68.7
Stabilizer Spread (Up Position) (in.)	46.5
Bucket Digging Force (lbs.)	3,740

Additional Equipment Available

- Deluxe Cabin With Heating & A/C
- Cabin Air Recirculation
- Front & Rear Windshield Washer/Wiper System (Cab Only)
- Deluxe Stereo System With CD Player, USB (Cab Only)
- Pre-heat Starting Aid
- Hand & Foot Throttle Control
- Tilt Steering
- Front Loader Valve And Joystick
- Hydraulic Draft & Position Control
- Adjustable Seat
- Lower Links & Telescopic Stabilizers
- Drawbar
- Flashers
- 7-Pin Implement Socket

