

XJ SERIES

LS Tractor

LS
Leading
Solution

XJ2025H

SMALL COMPACT TRACTORS

6-YEAR LIMITED WARRANTY. SEE DEALER FOR DETAILS

XJ SERIES

SMALL COMPACT TRACTORS

RECOMMENDED IMPLEMENTS/ ATTACHMENTS



LOADER:
High Capacity With
An Abundance Of
Standard Features



BACKHOE:
Excellent Capacity,
Smooth And
Consistent Operation
For Added Control



ROTARY CUTTER:
Durable Heavy Steel
Design Providing
Quality And Strength



BOX BLADE:
Features A Heavy
Welded Steel
Design For Use In
Demanding Applications

FEATURES

- *6 Year Warranty**
- *Eco-Friendly Tier 4, 24.7HP, 3 Cylinder Fuel Efficient Engine*
- *2 Range HST With Dual Pedals And Cruise Control*
- *Front Wheel Mechanical Assist 4wd*
- *Choice Of Industrial Or Turf Tires At No Additional Cost*
- *Available Quick Attach Front End Loader And Grille Guard*
- *Available Sub-Frame Mounted, Quick Attach 6' Backhoe*
- *Available 60" Mid-Mount Mower*
- *Available 50" Snow Blower*



Electric PTO Engagement
Provides Added Comfort



**Illuminated Dash With
Digital RPM**
Provides Excellent
Operator Visibility



Engine Compartment Access
Excellent Access For
Preventative Maintenance



Foldable ROPS
Provides Versatility



Standard Toolbox
Providing Storage



**Durable Front Loader
And Bucket**
High-Quality And Durable
Front Bucket



**Durable And Adjustable
Three Point**
Provides 1,433 lbs. Of
Lift Capacity



High Capacity Front Loader
Features 1,276 Lbs. Of Lift
Capacity At Pivot Pins



**Multiple Tire Options
Available**
Provides Tires For Nearly
All Applications

XJ2025H



SPECIFICATIONS

CATEGORY	
ENGINE	XJ2025H
Type	3 Cylinder-Indirect - injection, Water-cooled
Model (Tier 4)	Mitsubishi S3L2
Engine HP (gross)	24.7
PTO (HP)	18.5
Rated Speed (rpm)	2,500
Displacement-cu (in ³ .)	80.4
Fuel Tank Capacity (gal.)	6.6
Alternator (V-A)	12 - 50
DRIVE TRAIN	
Transmission	Hydrostatic Drive
No. Of Speed	2 Ranges
Brakes	Wet, Multi-disc
PTO	
Type	Independent
Rear (rpm)	Standard (540 rpm)
Mid (rpm)	Standard (2,000 rpm)
HYDRAULIC SYSTEM	
Lift Control System	Position
Implement Pump (gpm)	5.9
Steering Pump (gpm)	2.6
Steering	Hydrostatic Power Steering
Total Flow (gpm)	8.5
Category (3pt Hitch)	CAT I
Hitch Lift Capacity (lbs.) (Hitch End)	1,433
DIMENSION	
Overall Length (Bumper To Link in.)	103
Overall Width With Tires (in.)	44.9
Wheelbase (in.)	59
Height To Top Of ROPS (in.)	84.5
TIRE SIZE	
Front / Rear Industrial	23 x 8.5 - 12 / 33 x 12 - 16.5
Front / Rear Turf	23 x 8.5 - 12 / 33 x 12 - 16.5
WEIGHT	
Total Weight w/o Ballast (lbs.)	1,689

SNOW BLOWER	
TRACTOR APPLICATION	LS3150
Overall Width (in.)	XJ SERIES
Cutting Width (in.)	50
Cutting Height (in.)	49 3/4
Impeller Drive	20
Auger Drive	Chain #40
Auger Diameter (in.)	Worm Gear
Impeller Diameter (in.)	12 3/4
Number Of Blades On Impeller	15 3/4
Chute Rotation (deg.)	3
Adjustable Heavy Skid Shoes	Manual
	Yes

**All Specs and features are subject to change, and pictures could include optional equipment etc.*

FRONT END LOADER	
TRACTOR APPLICATION	LL2102
Bucket Size (in.)	XJ SERIES
Maximum Lift Height (in.)	50
Clearance With Attachment Dump (in.)	85.7
Reach At Maximum Height (in.)	63.3
Maximum Dump Angle (deg.)	25.1
Maximum Rollback Angle (deg.)	50
Digging Depth (in.)	38
Overall Heights In Carry Position (in.)	3.7
Lift Capacity (At Pivot Pin) (lbs.)	43.2
Breakout Force (At Pivot Pin) (lbs.)	1,276
Approx. Weight (Loader w/o Bucket) (lbs.)	1,687
	580

BACKHOE	
TRACTOR APPLICATION	LB1104
Digging Depth (in.)	XJ SERIES
Reach From Centerline Of Swing Pivot (in.)	79.3
Loading Height (in.)	113.3
Swing Arc (deg.)	56.9
Transport Height (in.)	150
Bucket Rotating (deg.)	75.3
Stabilizer Spread (Down Position) (in.)	163
Stabilizer Spread (Up Position) (in.)	87.8
Bucket Digging Force (lbs.)	55.7
	2,092

MID-MOUNT MOWER	
TRACTOR APPLICATION	LM3560
Cutting Width (in.)	XJ SERIES
Overall Width (in.)	60
Cutting Height Range (in.)	74
Deck Shell Thickness	1 to 4-1/8
Spindle Speed At Rated Engine(rpm)	10-Gauge (0.1345 in.) Grade 50 Sheet
Blade Tip Speed (ft./min)	2,842
Number Of Blades	18,000
Blade Length (in.)	3
Blade Width (in.)	21
Blade Thickness (in.)	2- 1/2
Shipping Weight Of Base 60" Deck (lbs.)	1/4
	450

Additional Equipment

- Power Steering
- Switch Operated Independent PTO, Rear & Mid (XJ2025)
- Foldable ROPS
- Rear Work light
- Hydraulic Position Control
- Differential Lock
- Draw bar
- Pre-Heat Starting Aid
- Safety Flashers & Turn Signals
- Fuel, Coolant Temperature, Tachometer & Hour Meter Gauges
- Pre-Heating, Parking Brake, Battery Charging, Engine Oil Pressure, PTO Operation And High Beam Operation And Warning Lights



LS Tractor

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | LSTractorUSA.com
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

